

United States Patent [19]**Saxe et al.**[11] **4,113,362**[45] **Sep. 12, 1978**

[54] **LIGHT VALVE, LIGHT VALVE
SUSPENSION MATERIALS AND
SUSPENSION THEREFOR**

[75] Inventors: **Robert L. Saxe**, New York; **Robert I. Thompson**, Plainview; **Matthew Forlini**, Ozone Park, all of N.Y.

[73] Assignee: **Research Frontiers Incorporated**, Plainview, N.Y.

[21] Appl. No.: **795,819**

[22] Filed: **May 11, 1977**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 604,410, Aug. 13, 1975, Pat. No. 4,025,163.

[51] Int. Cl.² **G02B 5/23**

[52] U.S. Cl. **350/362**

[58] Field of Search **350/150, 355, 356, 362**

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,531,185 9/1970 Buchsbaum et al. 350/362

3,788,729 1/1974 Lowell et al. 350/362

Primary Examiner—William L. Sikes

Attorney, Agent, or Firm—Jacobs & Jacobs

[57] **ABSTRACT**

A light valve including suspending materials which have an ability to prevent or substantially retard agglomeration of the particles in suspension during the application of a voltage to the suspension. The materials include aromatic esters which are derivable from aromatic alcohols, such as phenyl acetate, cresyl acetate, para-butylphenyl acetate, para-nonylphenyl acetate, and structurally similar compounds. The suspension also includes, as an additional suspending material, a polymer such as a branched polymeric coating material to coat the particles in suspension and act in combination with the aromatic ester suspending materials to prevent or substantially reduce agglomeration of the particles when a voltage is applied to the suspension. Other suspending materials such as non-aqueous liquids or solids may also form part of the suspending medium of this invention.

29 Claims, 4 Drawing Figures

